



MaxLOCK® CAM & GROOVE COUPLINGS FOR HOSE & PIPE

A



ADAPTOR

Female Thread: NPT, BSP or special thread as demand

B



COUPLER

Male Thread: NPT, BSP or special thread as demand

C



HOSE SHANK COUPLER

Be attached directly to uncoupled hose with any type of clamp or bands

D



COUPLER

Female Thread: NPT, BSP or special thread as demand

E



HOSE SHANK ADAPTOR

Be attached directly to uncoupled hose with any type of clamps or bands

F



ADAPTOR

Male Thread: NPT, BSP or special thread as demand

DC



DUST CAP

For adaptor type "A, E, F"

DP



DUST PLUG

For Coupler "B, C, D"



HANDLE WITH PIN

CAM ARM: Brass, Stainless Steel
Pin: Stainless Steel


8 Basic Parts

Available in Size

1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"

Material Of Body

1. Brass
2. Aluminium
3. Stainless Steel (By Investment Cast)
4. Polypropylene
5. Special material upon request



GASKET

Buna N

Buna N is standard. It is generally recommended for petroleum derivatives, neutral or slightly acidic salt solutions, alcohols, ethers, glycols, fats, oils and greases. This compound should give good service from -40°F to +250°F.

Neoprene

Recommended for alkaline and acid salt solutions and aldehydes such as for maldehyde. For food services, white neoprene is also available. Temperature recommended -40°F to +250°F.