



FIRE SLEEVE



Used to protect transformer lead protection, motor coil leads, component isolation, and power supply wiring. Voltage from 1.5 KV to 10 KV. It resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable. It provides excellent protection for industrial wires, cables, hoses (hydraulics), tube and pipes and also provides thermal insulation and personnel protection.

MATERIAL	Fiberglass, Silicone
WORKING TEMPERATURE	-75°C to +260°C
FLAMMABILITY	VW-1
MELTING POINT	+550°C
CUTTING TOOL	Scissors

SIZE < 2"

PART NO.	INSIDE DIAMETER		METER FOR SPOOL
	mm	inch	meter
MXFGS-0006	6	1/4	50
MXFGS-0008	8	5/16	50
MXFGS-0010	10	3/8	50
MXFGS-0011	11	7/16	50
MXFGS-0013	13	1/2	50
MXFGS-0016	16	5/8	50
MXFGS-0019	19	3/4	50
MXFGS-0022	22	7/8	50
MXFGS-0025	25	1	50
MXFGS-0029	29	1-1/8	50
MXFGS-0032	32	1-1/4	50
MXFGS-0035	35	1-3/8	50
MXFGS-0038	38	1-1/2	50
MXFGS-0041	41	1-5/8	50
MXFGS-0044	44	1-3/4	50
MXFGS-0048	48	1-7/8	50

SIZE > 2"

PART NO.	INSIDE DIAMETER		METER FOR SPOOL
	mm	inch	meter
MXFGS-0051	51	2	50
MXFGS-0057	57	2-1/4	50
MXFGS-0060	60	2-2/5	50
MXFGS-0064	64	2-1/2	50
MXFGS-0067	67	2-5/8	50
MXFGS-0070	70	2-3/4	50
MXFGS-0073	73	2-7/8	50
MXFGS-0076	76	3	50
MXFGS-0083	83	3-1/4	50
MXFGS-0089	89	3-1/2	50
MXFGS-0095	95	3-3/4	50
MXFGS-0102	102	4	50
MXFGS-0114	114	4-1/2	50
MXFGS-0121	121	4-3/4	50
MXFGS-0127	127	5	50
MXFGS-0152	152	6	50

* Other size and colours available on request