



The Right Connection®

HYDRAULIC COUPLINGS

E-Series Straight-Through Interchange Coupler (Female Threads)

FEATURES

- Straight-Through Pressure-Wash Interchange
- Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
- These couplers have no internal valves, providing maximum flow with minimum pressure drop.

CONSTRUCTION

- Machined components are manufactured using solid brass
- Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
- Nitrile (Buna-N) seals are standard

AVAILABLE OPTIONS

- Contact us for additional seal material options, pressure ratings and other technical information.

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/8"	1EF1-B	1/8"-27 NPTF	Brass	1.01	25.7	0.65	16.5	9/16"	0.06
1/8"	1EF1-S	1/8"-27 NPTF	303 Stainless	1.01	25.7	0.65	16.5	9/16"	0.05
1/4"	2EF2-B	1/4"-18 NPTF	Brass	1.40	35.6	0.96	24.4	13/16"	0.17
1/4"	2EF2-S	1/4"-18 NPTF	303 Stainless	1.40	35.6	0.96	24.4	13/16"	0.15
1/4"	2EBF2-B	1/4"-19 BSPP	Brass	1.40	35.6	0.96	24.4	13/16"	0.17
3/8"	3EF3-B	3/8"-18 NPTF	Brass	1.60	40.6	1.13	28.7	1"	0.26
3/8"	3EF3-S	3/8"-18 NPTF	303 Stainless	1.60	40.6	1.13	28.7	1"	0.24
3/8"	3EBF3-B	3/8"-19 BSPP	Brass	1.60	40.6	1.13	28.7	1"	0.26
1/2"	4EF4-B	1/2"-14 NPTF	Brass	1.96	49.8	1.27	32.3	1 1/8"	0.39
1/2"	4EF4-S	1/2"-14 NPTF	303 Stainless	1.96	49.8	1.27	32.3	1 1/8"	0.37
1/2"	4EBF4-B	1/2"-14 BSPP	Brass	1.96	49.8	1.27	32.3	1 1/8"	0.39
3/4"	6EF6-B	3/4"-14 NPTF	Brass	2.10	53.3	1.65	41.9	1 1/2"	0.62
3/4"	6EF6-S	3/4"-14 NPTF	303 Stainless	2.10	53.3	1.65	41.9	1 1/2"	0.57
3/4"	6EBF6-B	3/4"-14 BSPP	Brass	2.10	53.3	1.65	41.9	1 1/2"	0.62
1"	8EF8-B	1"-11 1/2 NPTF	Brass	2.36	59.9	2.02	51.3	1 3/4"	0.99
1"	8EF8-S	1"-11 1/2 NPTF	303 Stainless	2.36	59.9	2.02	51.3	1 3/4"	0.93
1"	8EBF8-B	1"-11 BSPP	Brass	2.36	59.9	2.02	51.3	1 3/4"	0.99
1 1/4"	10EF10-B	1 1/4"-11 1/2 NPTF	Brass	2.36	59.9	2.59	65.8	2 1/4"	1.38
1 1/4"	10EF10-S	1 1/4"-11 1/2 NPTF	303 Stainless	2.36	59.9	2.59	65.8	2 1/4"	1.38
1 1/2"	12EF12-B	1 1/2"-11 1/2 NPTF	Brass	2.89	73.4	3.18	80.8	2 3/4"	1.42
1 1/2"	12EF12-S	1 1/2"-11 1/2 NPTF	303 Stainless	2.89	73.4	3.18	80.8	2 3/4"	1.42
2"	16EF16-B	2"-11 1/2 NPTF	Brass	3.00	76.2	4.04	102.6	3 1/2"	4.70
2"	16EF16-S	2"-11 1/2 NPTF	303 Stainless	3.00	76.2	4.04	102.6	3 1/2"	4.72

- ⚠ Do Not Disconnect with pressure in line.
- We cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm