



## HYDRAULIC COUPLINGS

### K-Series ISO-A Interchange Coupler (Female Threads)

#### FEATURES

- Poppet style shut-off valve

#### CONSTRUCTION

- Machined components are manufactured using solid bar stock
- Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
- Steel componentry is plated using ROHS Compliant Trivalent Chrome.
- Steel coupler sleeves are hardened to resist deformation and maximize service life.
- Nitrile (Buna-N) seals are standard
- Couplers have a PTFE Anti-Extrusion ring.
- Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

#### AVAILABLE OPTIONS

- Contact us for all available option adders
- Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
- Kalrez® seal options include: 4079, 6375 and 7075
- Valve options include: Unvalved, actuator, steel, brass, 303 stainless steel and 316 stainless steel
- Locking sleeve option available
- Oxy-Clean treatment is available

#### COMPATIBILITY & INTERCHANGE DATA

- Interchangeable to ISO7241 Series 'A'
- Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
- Faster ANV, Hansen HA 15000, Safeway S56-Series

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1 1/4"	<b>10KF10</b>	1 1/4" - 11 1/2" NPT	Steel	4.61	117.0	2.76	70.0	2"	2.93
1 1/4"	<b>10KBF10</b>	1 1/4" - 11 BSPP	Steel	4.61	117.0	2.76	70.0	2"	2.93
1 1/2"	<b>12KF12</b>	1 1/2" - 11 1/2" NPT	Steel	5.24	133.0	3.33	84.5	2 3/8"	4.78
1 1/2"	<b>12KBF12</b>	1 1/2" - 11 BSPP	Steel	5.24	133.0	3.33	84.5	2 3/8"	4.78
2"	<b>16KF16</b>	2" - 11 1/2" NPT	Steel	6.50	165.0	3.94	100.0	3"	8.49
2"	<b>16KBF16</b>	2" - 11 BSPP	Steel	6.50	165.0	3.94	100.0	3"	8.49



**WARNING:** Cancer and Reproductive Harm

#### K Profiles

