


HYDRAULIC COUPLINGS

H-Series ISO-B Food Grade Silicone Flanged Coupler (Female Threads)



FEATURES	<ul style="list-style-type: none"> • Poppet style shut-off valves • Designed to prevent fluid loss when disconnected
CONSTRUCTION	<ul style="list-style-type: none"> • Machined components are manufactured using solid bar stock • Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life. • Silicone flanged sleeve • FDA FKM seals are standard • Redundant o-ring sealing system with PTFE backup ring • Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.
AVAILABLE OPTIONS	<ul style="list-style-type: none"> • Contact us for all available option adders
COMPATIBILITY & INTERCHANGE DATA	<ul style="list-style-type: none"> • Meets dimensional requirements of ISO 7241 Series B • Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/2"	D-4HF4-S-FSB	1/2"-14 NPTF	303 Stainless	2.86	72.6	2.52	64.0	1 1/16"	0.75
1/2"	D-4HF4-SS-FSB	1/2"-14 NPTF	316 Stainless	2.86	72.6	2.52	64.0	1 1/16"	0.75





HYDRAULIC COUPLINGS

H-Series ISO-B Food Grade Nylon Flanged Coupler (Female Threads)



FEATURES	<ul style="list-style-type: none"> • Poppet style shut-off valves • Designed to prevent fluid loss when disconnected
CONSTRUCTION	<ul style="list-style-type: none"> • Machined components are manufactured using solid bar stock • Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life. • Silicone flanged sleeve • FDA FKM seals are standard • Redundant o-ring sealing system with PTFE backup ring • Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.
AVAILABLE OPTIONS	<ul style="list-style-type: none"> • Contact us for all available option adders
COMPATIBILITY & INTERCHANGE DATA	<ul style="list-style-type: none"> • Meets dimensional requirements of ISO 7241 Series B • Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/2"	D-4HF4-S-FNS	1/2"-14 NPTF	303 Stainless	2.86	72.6	2.38	60.5	1 1/16"	0.75
1/2"	D-4HF4-SS-FNS	1/2"-14 NPTF	316 Stainless	2.86	72.6	2.38	60.5	1 1/16"	0.75



HYDRAULIC COUPLINGS

H-Series ISO-B Food Grade Nipple (Female Threads)



FEATURES	<ul style="list-style-type: none"> • Poppet style shut-off valves • Designed to prevent fluid loss when disconnected
CONSTRUCTION	<ul style="list-style-type: none"> • Machined components are manufactured using solid bar stock • Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life. • Steel componentry is plated using ROHS Compliant Trivalent Chrome. • Steel Nipples are hardened to provide heavy duty performance and resist brinelling.
AVAILABLE OPTIONS	<ul style="list-style-type: none"> • Contact us for all available option adders
COMPATIBILITY & INTERCHANGE DATA	<ul style="list-style-type: none"> • Meets dimensional requirements of ISO 7241 Series B • Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/2"	D-H4F4-SV-8	1/2"-14 NPTF	Steel	1.94	49.3	1.17	29.7	1 1/16"	0.20
1/2"	D-H4F4-S	1/2"-14 NPTF	303 Stainless	1.94	49.3	1.17	29.7	1 1/16"	0.24
1/2"	D-H4F4-SS	1/2"-14 NPTF	316 Stainless	1.94	49.3	1.17	29.7	1 1/16"	0.24