



OIL DISCHARGE HOSE 150 PSI

ODH 150

Used for delivery and transfer of a wide range of petroleum products up to 50% aromatic content and up to maximum working temperature 100°C (212°F)



TEMPERATURE RANGE	40°C to 100°C
TUBE	Black, smooth, nitrile rubber compounded
REINFORCEMENT	High strength synthetic cord plus anti-static copper wire
COVER	Black, smooth (wrapped finish) high grade chloroprene rubber, compound for an excellent resistance to weather, ozone, abrasion and oil
COILS	61 meter (200ft) continuous length; other length available on request

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE (Theoretical)		WEIGHT (Nominal)	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft
ODH150-0100	25	1	36.5	1-13/32	10	150	30	450	0.82	0.56
ODH150-0125	32	1¼	46	1-47/94	10	150	30	450	1.20	0.82
ODH150-0138	35	1⅝	48	1-57/64	10	150	30	450	1.29	0.88
ODH150-0150	38	1½	52	2-3/64	10	150	30	450	1.38	0.95
ODH150-0163	42	1⅝	53	2-3/32	10	150	30	450	1.50	1.00
ODH150-0175	45	1¾	60	2-23/64	10	150	30	450	1.69	1.16
ODH150-0200	51	2	64	2-1/2	10	150	30	450	1.78	1.22
ODH150-0225	57	2¼	70	2-49/64	10	150	30	450	1.96	1.34
ODH150-0238	60	2⅜	73	2-55/64	10	150	30	450	2.06	1.41
ODH150-0250	63	2½	78	2-59/64	10	150	30	450	2.32	1.59
ODH150-0300	76	3	90	3-1/2	10	150	30	450	2.75	1.88
ODH150-0350	90	3½	108	4-1/4	10	150	30	450	3.45	2.36
ODH150-0400	102	4	120	4-21/32	10	150	30	450	3.90	2.67
ODH150-0600	152	6	170	6-11/16	10	150	30	450	5.05	3.39

* Other size, pressure ratings and colours available on request