



OIL DISCHARGE HOSE 300 PSI

ODH 300

Mandrel built heavy oil discharge hose, excellent for used for transfer & delivery a wide range of petroleum products up to 50% aromatic content.



TEMPERATURE RANGE	40°C to 100°C
TUBE	Black, smooth, nitrile compounded
REINFORCEMENT	High tensile textile cords
COVER	Black, smooth (wrapped finish) high grade chloroprene rubber, compound for an excellent resistance to weather, ozone, abrasion and oil resistant, antistatic
COILS	61 meter (200ft) continuous length; other length available on request
SAFETY FACTOR	4 : 1

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE (Theoretical)		WEIGHT (Nominal)	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft
ODH300-0100	25	1	35	1-3/8	20	300	80	1200	0.95	0.64
ODH300-0200	51	2	65	2-9/16	20	300	80	1200	1.77	1.19
ODH300-0250	63	2 1/2	80	3-3/16	20	300	80	1200	2.72	1.82
ODH300-0300	76	3	93	3-21/32	20	300	80	1200	2.86	1.92
ODH300-0400	102	4	120	4-47/64	20	300	80	1200	4.85	3.25
ODH300-0500	127	5	149	5-7/8	20	300	80	1200	6.46	4.33
ODH300-0600	152	6	174	6-55/65	20	300	80	1200	7.64	5.00

* Other size, pressure ratings and colours available on request