



**WATER DISCHARGE  
HOSE 150 PSI**

**WDH 150**

Mandrel built heavy water discharge hose, it handles sewage, waste water, mud, etc



TEMPERATURE RANGE	-40°C to +85°C
CONSTRUCTION TUBE	Black, smooth, synthetic rubber resistant to water with ph value 5 to 8
REINFORCEMENT	High strength synthetic cord
COVER	Black, smooth (wrapped finish) synthetic rubber, abrasion and weathering
COILS	61 meter (200ft) continuous length for 4" and below

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE (Theoretical)		WEIGHT (Nominal)	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft
WDH150-0125	32	1¼	44	1.63	10	150	30	450	0.39	0.26
WDH150-0150	38	1½	50	1.97	10	150	30	450	0.54	0.36
WDH150-0200	51	2	64	2.53	10	150	30	450	0.77	0.52
WDH150-0250	63	2½	78	3.17	10	150	30	450	1.04	0.70
WDH150-0300	76	3	92	3.63	10	150	30	450	1.06	0.71
WDH150-0338	86	3¾	99	3.91	10	150	30	450	1.95	1.31
WDH150-0350	90	3½	103	4.03	10	150	30	450	1.98	1.33
WDH150-0400	102	4	110	4.72	10	150	30	450	2.09	1.40
WDH150-0450	115	4½	132	5.20	10	150	30	450	2.67	1.79
WDH150-0500	127	5	144	5.63	10	150	30	450	3.72	2.49
WDH150-0600	152	6	171	6.75	10	150	30	450	5.23	3.50
WDH150-0800	203	8	227	8.94	10	150	30	450	9.16	6.14
WDH150-1000	254	10	280	11.13	10	150	30	450	12.53	8.40
WDH150-1200	305	12	325	13.00	10	150	30	450	16.41	11.00
WDH150-1400	350	14	370	14.75	10	150	30	450	21.00	14.07
WDH150-1600	400	16	420	16.50	10	150	30	450	27.29	18.28

\* Other size, pressure ratings and colours available on request