




MaxLOCK®
GROUND
JOINT



Features:

- Positive metal-to-polymer seal
- Leakproof seal forms when the metal head of the stem makes contact with the patented polymer seat in the spud
- Non-metallic polymer seat resists most chemicals found in manufacturing facilities
- Recommended for steam service up to **450°F (232°C)**
- Easy to seal
- Use with Maxlock® clamps

MAXLOCK® GROUND JOINT CLAMP 2 BOLT (MG-C2)	SIZE	OPTIONAL QTY
	1/4"	100
	3/8"	100
	1/2"	100
	3/4"	50

PART NUMBER



MODEL	PART NO.	MATERIAL	HOSE ID	HOSE OD
MG Maxlock® Ground Joint	C2 Clamp 2 Bolt	PS Plated Steel	8 = 1/4" 10 = 3/8" 15 = 1/2" 20 = 3/4"	A = 36/64" ~ 42/64" B = 44/64" ~ 56/64" C = 52/64" ~ 60/64" D = 60/64" ~ 1-4/64" E = 1-4/64" ~ 1-12/64" F = 1-10/64" ~ 1-20/64" G = 1-20/64" ~ 1-32/64" H = 1-32/64" ~ 1-44/64"
	C4 Clamp 4 Bolt	SS Stainless Steel 316 BR Brass		