





**MaxLOCK®**  
**GROUND**  
**JOINT**



**Features:**

- Positive metal-to-polymer seal
- Leakproof seal forms when the metal head of the stem makes contact with the patented polymer seat in the spud
- Non-metallic polymer seat resists most chemicals found in manufacturing facilities
- Recommended for steam service up to **450°F (232°C)**
- Easy to seal
- Use with Maxlock® clamps

MAXLOCK® GROUND JOINT CLAMP 4 BOLT (MG-C4)	SIZE	OPTIONAL QTY
	1"	25
	1-1/4"	20
	1-1/2"	10
	2"	10
	2-1/2"	5
	3"	5

**PART NUMBER**



MODEL	PART NO.	MATERIAL	HOSE ID	HOSE OD
<b>MG</b> Maxlock® Ground Joint	<b>C2</b> Clamp 2 Bolt	<b>PS</b> Plated Steel	<b>25</b> = 1"	<b>A</b> = 1-34/64" ~ 1-46/64" <b>B</b> = 1-44/64" ~ 1-60/64" <b>C</b> = 1-60/64" ~ 2-8/64" <b>D</b> = 1-32/64" ~ 1-50/64" <b>E</b> = 1-50/64" ~ 2-6/64" <b>F</b> = 2-8/64" ~ 2-24/64" <b>G</b> = 1-52/64" ~ 2" <b>H</b> = 2" ~ 2-14/64" <b>I</b> = 2-12/64" ~ 2-24/64" <b>J</b> = 2-24/64" ~ 2-36/64" <b>K</b> = 2-36/64" ~ 2-48/64" <b>L</b> = 2-22/64" ~ 2-34/64" <b>M</b> = 2-32/64" ~ 2-50/64" <b>N</b> = 2-48/64" ~ 3-4/64" <b>O</b> = 3-6/64" ~ 3-28/64" <b>P</b> = 3-6/64" ~ 3-28/64" <b>Q</b> = 3-32/64" ~ 3-60/64" <b>R</b> = 3-32/64" ~ 3-60/64" <b>S</b> = 3-52/64" ~ 4-4/64" <b>T</b> = 4-4/64" ~ 4-28/64"
	<b>C4</b> Clamp 4 Bolt	<b>SS</b> Stainless Steel 316	<b>32</b> = 1-1/4" <b>40</b> = 1-1/2" <b>50</b> = 2" <b>65</b> = 2-1/2" <b>80</b> = 3"	
		<b>BR</b> Brass		