







**MaxLOCK®**  
**GROUND**  
**JOINT**



**Features:**

- Positive metal-to-polymer seal
- Leakproof seal forms when the metal head of the stem makes contact with the patented polymer seat in the spud
- Non-metallic polymer seat resists most chemicals found in manufacturing facilities
- Recommended for steam service up to **450°F (232°C)**
- Easy to seal
- Use with Maxlock® clamps

MAXLOCK® GROUND JOINT COUPLING with FEMALE SPUD (MG-JC)	HOSE SHANK X NPT	OPTIONAL QTY
 <b>Plated Iron / Steel</b>	1/4"	100
	3/8"	100
	1/2"	100
	1/2" x 3/4"	50
	3/4"	50
 <b>316 Stainless Steel</b>	1"	50
	1 1/4"	25
	1 1/2"	25
 <b>Brass</b>	2"	10
	2 1/2"	5
	3"	5
	4"	5
	6"	2

**!** \* 1/4" 3/8" and 6" available only with copper seat spuds  
 \*\* not to be used with #250, #275 or #306 Maxlock® clamps

**PART NUMBER**



MODEL	PART NO.	MATERIAL	COUPLING SIZE
<b>MG</b> Maxlock® Ground Joint	<b>JS</b> - Joint Stem	<b>PS</b> Plated Steel	<b>8</b> = 1/4"
	<b>JC</b> - Joint Coupling		<b>10</b> = 3/8"
	<b>WN</b> - Wing Nut		<b>15</b> = 1/2"
	<b>FS</b> - Female Spud	<b>SS</b> Stainless Steel 316	<b>20</b> = 3/4"
	<b>MP</b> - Male Spud		<b>25</b> = 1"
	<b>DS</b> - Double Spud	<b>BR</b> Brass	<b>32</b> = 1-1/4"
	<b>FA</b> - Female NPT Adapter		<b>40</b> = 1-1/2"
	<b>MA</b> - Male NPT Adapter		<b>50</b> = 2"
	<b>MS</b> - Male Stem		<b>65</b> = 2-1/2"
			<b>100</b> = 4"
			<b>150</b> = 6"