




MaxLOCK®
GROUND JOINT



Features:

- Positive metal-to-polymer seal
- Leakproof seal forms when the metal head of the stem makes contact with the patented polymer seat in the spud
- Non-metallic polymer seat resists most chemicals found in manufacturing facilities
- Recommended for steam service up to **450°F (232°C)**
- Easy to seal
- Use with Maxlock® clamps

MAXLOCK GROUND JOINT MALE NPT ADAPTERS (MG-MA)	SIZE	OPTIONAL QTY
	1/4"	100
	3/8"	100
	1/2"	100
	1/2" x 3/4"	50
	3/4"	50
	1"	50
	1 1/4"	25
	1 1/2"	25
	2"	10
	2 1/2"	5
3"	5	
4"	5	
6"	2	

* supplied with wing nut, as shown.
 ** design to fit the Maxlock® Ground Joint Female Spuds.
 *** uses a special wing nut.

PART NUMBER



MODEL	PART NO.	MATERIAL	COUPLING SIZE
MG Maxlock Ground Joint	JS	PS	8 = 1/4"
	JC	Plated Steel	10 = 3/8"
	WN	SS	15 = 1/2"
	FS	Stainless Steel 316	20 = 3/4"
	MP		25 = 1"
	DS	BR	32 = 1-1/4"
	FA	Brass	40 = 1-1/2"
	MA		50 = 2"
	MS		65 = 2-1/2"
			100 = 4"
			150 = 6"