



# MaxLOCK® QUICK ACTING COUPLINGS

**Features:**

- Quick Acting Coupling is rated to **300 psi** at ambient temperature (**70°F**)

Quick Acting Coupling Male with Female NPT	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Female with Female NPT	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Male with Male NPT	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/8" 1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Female with Male NPT	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/8" 1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25

## PART NUMBER



MODEL	MATERIAL	BODY SIZE	THREAD SIZE
<b>MXQA</b> Maxlock Quick Acting Couplings	<b>PS</b> Plated Steel	<b>FEMALE</b>	
		<b>F10</b>	= 1/8"
		<b>F15</b>	= 1/2"
		<b>MALE</b>	
		<b>M10</b>	= 1/8"
		<b>M15</b>	= 1/2"
	<b>SS</b> Stainless Steel 316	<b>FEMALE NPT</b>	
		<b>F10</b>	= 1/8"
		<b>F15</b>	= 1/2"
		<b>F20</b>	= 3/4"
		<b>F25</b>	= 1"
		<b>MALE NPT</b>	
<b>M10</b>	= 1/8"		
<b>M15</b>	= 1/2"		
<b>BR</b> Brass	<b>MALE NPT</b>		
	<b>M10</b>	= 1/8"	
	<b>M15</b>	= 1/2"	
	<b>M20</b>	= 3/4"	
		<b>M25</b>	= 1"



# MaxLOCK® QUICK ACTING COUPLINGS

**Features:**

- Quick Acting Coupling is rated to **300 psi** at ambient temperature (**70°F**)

Quick Acting Coupling Male with Hose End	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/8"	3/8"	25
	1/2"	1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Female with Hose End	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/8"	3/8"	25
	1/2"	1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Male Locking with Hose End	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25
Quick Acting Coupling Male Locking with Male NPT	BODY SIZE	THREAD SIZE	OPTIONAL QTY
	1/2"	3/8"	25
		1/2"	25
		3/4"	25
		1"	25

## PART NUMBER



MODEL	MATERIAL	BODY SIZE	THREAD SIZE
<b>MXQA</b> Maxlock Quick Acting Couplings	<b>PS</b> Plated Steel	<b>MALE LOCKING</b> ML15 = 1/2"	<b>HOSE END</b> H10 = 1/8"
			H15 = 1/2"
	<b>SS</b> Stainless Steel 316	<b>MALE</b> M10 = 1/8" M15 = 1/2"	H20 = 3/4"
			H25 = 1"
	<b>BR</b> Brass	<b>FEMALE</b> F10 = 1/8" F15 = 1/2"	<b>MALE NPT</b> M10 = 1/8"
			M15 = 1/2" M20 = 3/4" M25 = 1"