





MaxLOCK® SAFETY HOSE CABLE / WHIPCHECK

Features:

- Must be installed in the extended position (no slack)
- Cable reaches across hose fittings to provide standby safety for hose
- Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose
- No tools needed - easy to install and remove
- Cables shipped with safety restraint labels attached
- Highly resistant to rust and corrosion
- Minimizes damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly

Hose to Tool Service	SIZE	HOSE ID	LENGTH	MAXIMUM WORKING PRESSURE (psi)
	1/8"	1/2" - 1 1/4"	20 1/4"	200
	3/16"	1/2" - 2"	28"	200
	1/4"	1 1/2" - 3"	38"	200
	3/8"	4"	44"	200

Hose to Hose Service	SIZE	HOSE ID	LENGTH	MAXIMUM WORKING PRESSURE (psi)
	1/8"	1/2" - 1 1/4"	20 1/4"	200
	3/16"	1/2" - 2"	28"	200
	1/4"	1 1/2" - 3"	38"	200
	3/8"	4"	44"	200

PART NUMBER



MODEL	PART NO.	MATERIAL	COUPLING SIZE
MW Maxlock Whipcheck	HT Hose to Tool	SS Stainless Steel 304	5 = 3/16"
	HH Hose to Hose		6 = 1/8"
		CS Galvanized Carbon Steel	8 = 1/4"
			10 = 3/8"