



AIR HOSE

OHIO-3210

Heavy duty air supply line. Ideal for rough applications in mining, construction and hire industries.



| | |
|-------------------|---|
| TEMPERATURE RANGE | -20°C to +100°C |
| CONSTRUCTION TUBE | Black, SBR / NR |
| REINFORCEMENT | High strength synthetic polyester braided (3 ply) |
| COVER | Black smooth synthetic rubber, abrasion and weather resistant |
| SAFETY FACTOR | 4 : 1 |
| COLOUR | Black |
| BRANDING | with OHIO - 3210 W.P. 300 PSI printing |

| PART NO. | INTERNAL DIAMETER | | EXTERNAL DIAMETER | | WORKING PRESSURE | | BENDING RADIUS (mm) | AVERAGE WEIGHT | |
|-------------------|-------------------|-----|-------------------|-----|------------------|-----|---------------------|----------------|------|
| | inch | mm | inch | mm | bar | psi | | lb/ft | kg/m |
| OHIO-3210 AH-0050 | 1/2 | 13 | 15/16 | 23 | 20 | 300 | 102 | 0.26 | 0.38 |
| OHIO-3210 AH-0075 | 3/4 | 19 | 1-1/16 | 32 | 20 | 300 | 153 | 0.46 | 0.69 |
| OHIO-3210 AH-0100 | 1 | 25 | 1-1/2 | 38 | 20 | 300 | 201 | 0.59 | 0.87 |
| OHIO-3210 AH-0125 | 1-1/4 | 32 | 1-3/4 | 45 | 20 | 300 | 248 | 0.72 | 1.07 |
| OHIO-3210 AH-0150 | 1-1/2 | 38 | 1-11/16 | 52 | 20 | 300 | 261 | 0.96 | 1.42 |
| OHIO-3210 AH-0200 | 2 | 51 | 2-5/8 | 67 | 20 | 300 | 305 | 1.41 | 2.39 |
| OHIO-3210 AH-0250 | 2-1/2 | 63 | 3-5/32 | 80 | 20 | 300 | 386 | 1.91 | 2.81 |
| OHIO-3210 AH-0300 | 3 | 76 | 3-21/32 | 93 | 20 | 300 | 455 | 2.24 | 3.33 |
| OHIO-3210 AH-0400 | 4 | 102 | 4-23/32 | 120 | 20 | 300 | 736 | 3.18 | 4.72 |

*Other size, pressure ratings and colours available on request