



WATER HOSE

OHIO-3210

A heavy duty robust rubber hose for application in shipbuilding, refining, mining, construction industries and petrol chemical industries. Exceeds BS5118 type 2.



TEMPERATURE RANGE	-30°C to +100°C
CONSTRUCTION TUBE	Black, SBR/NR, resistant to oil mist
REINFORCEMENT	High strength synthetic polyester braided (3 ply)
COVER	Blue, smooth synthetic rubber, abrasion and weather resistant
SAFETY FACTOR	4 : 1
COLOUR	Blue
BRANDING	with OHIO - 3210 W.P. 300PSI printing

PART NO.	INTERNAL DIAMETER		EXTERNAL DIAMETER		WORKING PRESSURE		BENDING RADIUS (mm)	AVERAGE WEIGHT	
	inch	mm	inch	mm	bar	psi		lb/ft	kg/m
OHIO-3210 WH-0050	1/2	13	15/16	23	20	300	102	0.26	0.38
OHIO-3210 WH-0075	3/4	19	1-1/16	32	20	300	153	0.46	0.69
OHIO-3210 WH-0100	1	25	1-1/2	38	20	300	201	0.59	0.87
OHIO-3210 WH-0125	1-1/4	32	1-3/4	45	20	300	248	0.72	1.07
OHIO-3210 WH-0150	1-1/2	38	1-15/16	52	20	300	261	0.96	1.42
OHIO-3210 WH-0200	2	51	2-5/8	67	20	300	305	1.41	2.39
OHIO-3210 WH-0250	2-1/2	63	3-5/32	80	20	300	386	1.91	2.81
OHIO-3210 WH-0300	3	76	3-21/32	93	20	300	455	2.24	3.33
OHIO-3210 WH-0400	4	102	4-23/32	120	20	300	736	3.18	4.72

*Other size, pressure ratings and colours available on request