



The Right Connection®

## PNEUMATIC COUPLINGS

### N-Series Bowes Interchange Gender-Change Union

USE	<ul style="list-style-type: none"> <li>Gender-change union with coupler to coupler configuration</li> </ul>
SPECIFICATIONS	<ul style="list-style-type: none"> <li>Conforms to MIL-C-3486 and A-A-50431A standards</li> </ul>
CONSTRUCTION	<ul style="list-style-type: none"> <li>Machined components are manufactured using solid bar stock</li> </ul>
AVAILABLE OPTIONS	<ul style="list-style-type: none"> <li>316 stainless steel available in some versions upon request</li> </ul>
COMPATIBILITY & INTERCHANGE DATA	<ul style="list-style-type: none"> <li>Bowes Interchange Bayonet Style</li> <li>Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock</li> </ul>

SIZE	PART NUMBER	CONFIGURATION	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/2"	<b>4N4N</b>	Coupler to Coupler	Steel	3.26	82.8	1.33	33.8	-	0.30



It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

**WARNING:** Cancer and Reproductive Harm

