



**HEAVY DUTY OIL SUCTION & DISCHARGE DOCK HOSE**

**DH 300**



Heavy Duty Oil Suction & Discharge Dock Hose is designed for loading and unloading of petroleum based products of up to 50% aromatic content. Suitable for bunkering services between docks and ships under all types of services condition.

TEMPERATURE RANGE	-40 °C to +100 °C
CONSTRUCTION TUBE	Black, Oil Resistance Nitrile Rubber, Smooth Bore
REINFORCEMENT	High tensile synthetic cord incorporating wire helix
COVER	Black, oil, abrasion, ozone and weather resistance chloroprene rubber with orange longitudinal stripe
SAFETY FACTOR	Minimum 4 : 1
HOSE ASSEMBLIES FULLY CONFORM TO	BS 1435 1987 Type S15

PART NO	I.D.	O.D.	WORKING PRESSURE	TEST PRESSURE	BENDING RADIUS	HOSE WEIGHT	SWAGED FITTINGS WEIGHT
	mm	mm	psi	psi	mm/mtr	kg/mtr	kg/hose
DH300-0100	102	126	300	450	508	7.00	20.4
DH300-0150	152	182	300	450	914	15.7	31.4
DH300-0200	203	237	300	450	1219	21.2	64.0