



OIL SUCTION AND DISCHARGE HOSE 225 PSI

OSD225

Tank truck, tank wagon suction and delivery hose; it withstands the full vacuum; used for a wide range of petroleum products up to 50% aromatic content.



TEMPERATURE RANGE	-40 °C to +100 °C
CONSTRUCTION TUBE	Black, smooth, nitrile rubber compound
REINFORCEMENT	High strength synthetic cord plus helix and anti-static copper wire
COVER	Black, smooth (wrapped finish) high grade chloroprene rubber, compounded for an excellent resistance to weather, ozone abrasion and oil
COILS	61 meter (200ft) continuous length; other length available on request
BRANDING	Red transfer tape with negative text
SAFETY FACTOR	4 : 1

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS (mm)	WEIGHT (nominal) kg/m
	mm	inch	mm	inch	bar	psi	bar	psi		
OSD225-0200	51	2	62	2.44	15	225	60	900	223	2.04
OSD225-0250	63	2-1/2	77	3.01	15	225	60	900	275	3.20
OSD225-0300	76	3	92	3.62	15	225	60	900	328	3.38
OSD225-0350	90	3-1/2	104	4.94	15	225	60	900	396	4.02
OSD225-0400	102	4	120	4.72	15	225	60	900	477	5.80
OSD225-0500	127	5	147	5.79	15	225	60	900	669	7.78
OSD225-0600	152	6	172	6.77	15	225	60	900	803	7.23
OSD225-0800	203	8	227	8.94	15	225	60	900	1090	10.66

*Other size, pressure ratings and colours available on request